ACTIVE series

G5WP

12.2MP | 4X Zoom | Waterproof

Available Colors:

More get-up, More go

The sturdy metal housing contains your favorite high-tech features along with an internal zoom lens to keep things out of the way so you can stay on the move. There's even a waterproof model so the fun doesn't have to stop at the water's edge.

- **Pan-Capture Panorama**
- **Slim Body**
- **Waterproof**

camera features

G5WP

face detection
Automatically focuses and optimizes exposure for sharp, brilliant pictures.

high dynamic range
Adjusts the camera's exposure providing more picture detail.

blink detection
Alerts you if a subject's eyes were closed when the photo was snapped.

face auto-exposure
Automatically adjusts exposure around faces in a pictures.

optical zoom
Optical zoom lenses actually "move" you closer to the subject of the photograph.

auto-brightness
The LCD screen adjusts to the existing lighting conditions.

electronic image stabilization
Overcomes camera shake for clearer pictures.

auto scene
Automatically determines the appropriate scene type.

pan-capture panorama
Wide-view photos are produced by panning the camera across to create a seamless panoramic picture.

waterproof
Waterproof seals and gaskets keep water out so you can take advantage of crisp, clear pictures in and out of the water.

specifications*

	G5WP
Effective Image Sensor Pixels	12.2 Megapixels
Image Sensor	12.4 Megapixels [1/2.33" Charge Coupled Device (CCD)]
LENS	
Focal Length F =	6.75 mm (Wide) — 27 mm (Tele)
[35mm film equivalent]	[38 mm (Wide) — 152 mm (Tele)]
F number	f / 3.5 (Wide) — f / 5.15 (Tele)
Lens Construction	14 elements in 11 groups
Optical Zoom	4x
Focusing Range	Normal: (Wide) 23.6 in. ~ ∞ / 60 cm ~ ∞ , (Tele) 31.5 in. ~ ∞ / 80 cm ~ ∞ Macro: (Wide) 2.3 in. ~ 31.5 in. / 6 cm ~ 80 cm, (Tele) 31.5 in. ~ ∞ / 80 cm ~ ∞
Digital Zoom	4.5x Digital Zoom (Combined Zoom: 18x)
Still Image size	**12MP:** 4000×3000, (3:2) **10MP:** 4000×2672 , (16:9) **9MP:** 4000×2248, **10MP:** 3648×2736, **8MP:** 3264×2448 **5MP:** 2560×1920, **3MP:** 2048×1536, **0.3MP:** 640×480
Movie size	640×480pixels:30fps / 15fps, 320×240pixels:30fps / 15fps
Waterproof	Up to 5m underwater, Equivalent to JIS/IEC (IPX8)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
FILE FORMAT **Still Image**	Exif 2.2 (JPEG)
Movie	Movie Format: QuickTime Motion JPEG, Audio: G.711
Audio	WAVE [Monaural] (Max 60 seconds)
Shooting Modes	Auto, Manual, ASCN, Scene (Portrait, Image Stabilization, Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks Glass, Museum, Landscape, Night Landscape & Portrait), Underwater photography & movie, Panorama, Movie
LCD Display	2.7 inch (230,400 pixels)TFT-LCD Auto Adjust Brightness LCD
ISO Sensitivity	Auto, ISO 80 / 100 / 200 / 400 / 800 / 1600
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection + Face AE, AF Assist Light (On / Off), HDR
Exposure Metering Method	Artificial Intelligence AE (Ai AE), Center-weighted Average, Spot (Fixed to center of frame)
Exposure Control Method	Program AE (AE-lock available)
Exposure Compensation	± 2 EV in 1/3 Step increments
Shutter Speed	4 ~ 1/2000 seconds (Manual: 30 seconds)
Continuous Shooting	Approx. 1.39 fps (Large / Fine Mode)
Playback Modes	Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible) Zoom (Approx. 2x ~ 8x), Audio, Histogram Display
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, CWF, Incandescent, Manual
Internal Flash (Shooting Range)	Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro Gno. 5.5 (ISO 100)
Shooting Range	(Wide) Approx. 19.6 in. ~ 173.2 in. / 0.5 m ~ 4.4 m (Tele) Approx. 31.4 in. ~ 118.1 in. / 0.8 m ~ 3.0 m (ISO 800)
Recording Media	Internal Memory: 16 MB, SD Card / SDHC Card (Up to 16 GB support)
Other Features	PictBridge, ExifPrint Support, Multi-language Support, Red-eye Removal, High Dynamic Range
Jacks	USB2.0 / AV-OUT (Integrated Proprietary Connector)
Power	Rechargeable Lithium-ion Battery GB-10 (D016), 3.7V 700mAh
Shooting Capability	Approx. 180 shots (based on CIPA Standards)
Operation Environment	Temperature: 32 ~ 104 F / 0 ~ 40°C, Humidity: 0 ~ 90%
Dimensions (W x H x D)	3.8 in. × 2.4 in. × 0.8 in. / 95.8 mm × 62 mm × 20.5 mm
Weight	Approx. 4.4oz. / 125g (Body only)
Supplied Accessories	Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Feature Guide, Warranty Card

set up information

COLOR	SKU#	UPC	GIFT BOX WEIGHT (lbs)	GIFT BOX WxLxH (in)
Graphite Gray	DSC-G5WP-GG-US-1	810027015969	1.19	5.83 x 5.47 x 2.2
Ocean Blue	DSC-G5WP-OB-US-1	810027015938	1.19	5.83 x 5.47 x 2.2
Raspberry Red	DSC-G5WP-RR-US-1	810027016249	1.19	5.83 x 5.47 x 2.2

Exclusive Digital Camera Licensee

*For complete specifications, visit www.general-imaging.com/us/

Design and specifications subject to change without notice. Selection, offers and programs may vary. See your General Imaging representative for complete details. Corporate names, trademarks stated herein are the properties of their respective companies. Copyright © 2010 General Imaging Company. All rights reserved.

general imaging™